

View Online at <https://aerobasegroup.com/nsn/5315-01-595-1311>

**First End Style:**

Chamfered

**Second End Style:**

Square

**Hole Arrangement Style:**

One end w/two drilled holes

**First Hole Diameter:**

0.252 inches

**Second Hole Diameter:**

0.125 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.500 inches

**Center To Center Distance Between Holes:**

0.444 inches

**Pinlength:**

4.500 inches

**Pindiameter:**

0.748 inches

**End Application:**

Mk 6 various models

**First End Taper Length:**

0.062 inches

**Second End Relationship With First End:**

Not identical

**First End Taper Angle:**

45.0 degrees

**Surface Finish:**

125.0 microinches

**Angle Between Centerline Of Holes:**

45.0 degrees

**Product Name:**

Pin, latch

**Special Features:**

Next higher assembly ammo hoist, mk6

**Material:**

Copper alloy 630

**Material Specification:**

Acda 630 assn standard single material response

**Surface Treatment:**

Oxide and oil

**Surface Treatment Specification:**

Mil-f-495 federal specification 1st treatment response and mil-l-3150 federal specification 2nd treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-f-495 spec.