

View Online at <https://aerobasegroup.com/nsn/5315-01-596-2400>

**Head Diameter:**

0.750 inches

**Shank Diameter:**

0.300 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 16.000 inches and 16.020 inches

**Actuation Type:**

Push

**Shear Strength:**

28500 double pound

**Shoulder To Head End Distance:**

1.580 inches

**Pin Center To Handle End Distance:**

1.870 inches

**Detent To Tapered End Distance:**

0.490 inches

**Product Name:**

Pin, quick release positive locking, single acting

**Material:**

Stainless steel spindle

**Material Specification:**

Astma484 national std/spec all material responses or astm a581/582 national std/spec all material responses or astm a240 national std/spec all material responses or ams5513 national std/spec all material responses or ams5516 national std/spec all material responses or ams5640 national std/spec all material responses collar

**Surface Treatment:**

Passivate spring

**Surface Treatment Specification:**

Mil-a-8625 military specification 3rd treatment response or mil-c-5541 military specification 3rd treatment response button

**Style Designator:**

L handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-a-8625 spec.