NSN 5315-01-597-5354

Headed Grooved Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-597-5354

| First End Style:ChamferedHead Style:Flat chamferDiameter:Between 0.092 inches and 0.093 inchesEffective Length:Between 0.095 inches and 0.105 inchesUndercut Diameter:Between 0.061 inches and 0.067 inchesUnder Head Length:Between 0.080 inches and 0.067 inchesUndercut Width:Between 0.080 inches and 0.090 inchesEnd Application:Nt64 enginePin Head Diameter:Between 0.180 inches and 0.190 inchesProduct Name:Pin, straight, d-headedHeight:0.076 inchesMaterial:Steel comp 4140Material:Steel comp 4140Material Specification:Ams 6382 assn standard single material responseSurface Treatment:NickelStel Consignator:GrooveShelf Liffe:N/aDint of Measure:I'PinStel Zignator:Fig:Ans 120Stel Zignator:Stel Zignator:Stel Zignator:Stel Zignator:Stel Zignator:Stel Zignator:PinStel Zignator:PinStel Zignator:Stel Zignator: | |
|---|--|
| Head Style: Flat chamfer Diameter: Between 0.092 inches and 0.093 inches Effective Length: Between 0.095 inches and 0.105 inches Undercut Diameter: Between 0.061 inches and 0.067 inches Under Head Length: Between 0.430 inches and 0.440 inches Under Head Length: Between 0.430 inches and 0.090 inches End Application: Nt64 engine Pin Head Diameter: Between 0.180 inches and 0.190 inches Product Name: Pin, straight, d-headed Height: 0.076 inches Material Steel comp 4140 Material Specification: Arms 6382 assn standard single material response Surface Treatment: Nickel Surface Treatment Specification: Arms 2404 assn standard single treatment response Style Designator: Groove Shelf Life: N/a Unit Of Measure: Temiltarization: No Figig: | First End Style: |
| Flat chamfer Diameter: Between 0.092 inches and 0.093 inches Effective Length: Between 0.095 inches and 0.105 inches Undercut Diameter: Between 0.061 inches and 0.067 inches Under Head Length: Between 0.430 inches and 0.440 inches Undercut Width: Between 0.080 inches and 0.090 inches End Application: Nt64 engine Pin Head Diameter: Between 0.180 inches and 0.190 inches Product Name: Pin, straight, d-headed Height: 0.076 inches Material: Steel comp 4140 Material Specification: Ams 6382 assn standard single material response Surface Treatment: Nickel Surface Treatment Specification: Ams 2404 assn standard single treatment response Style Designator: N/a Unit Of Measure: N/a Fig: | Chamfered |
| Diameter:Diameter:Between 0.092 inches and 0.093 inchesEffective Length:Between 0.095 inches and 0.105 inchesUndercut Diameter:Between 0.061 inches and 0.067 inchesUnder Head Length:Between 0.430 inches and 0.440 inchesUndercut Width:Between 0.080 inches and 0.090 inchesEnd Application:Nt64 enginePin Head Diameter:Between 0.180 inches and 0.190 inchesProduct Name:Pin, straight, d-headedHeight:0.076 inchesMaterial:Steel comp 4140Material Specification:Ams 6382 assn standard single material responseSurface Treatment:NickelSurface Treatment Specification:Ams 2404 assn standard single treatment responseStyle Designator:GrooveShelf Life:N/aUnit Of Measure:-Demilitarization:NoFig: | Head Style: |
| Between 0.092 inches and 0.093 inches | Flat chamfer |
| Effective Length: Between 0.095 inches and 0.105 inches Undercut Diameter: Between 0.061 inches and 0.067 inches Under Head Length: Between 0.430 inches and 0.440 inches Undercut Width: Between 0.080 inches and 0.090 inches End Application: Nt64 engine Pin Head Diameter: Between 0.180 inches and 0.190 inches Product Name: Pin, straight, d-headed Height: 0.076 inches Material: Steel comp 4140 Material Specification: Ams 6382 assn standard single material response Surface Treatment: Nickel Surface Treatment Specification: Ams 2404 assn standard single treatment response Style Designator: Groove Shelf Life: N/a Unit Of Measure: Demilitarization: No | Diameter: |
| Between 0.095 inches and 0.105 inches Undercut Diameter: Between 0.061 inches and 0.067 inches Under Head Length: Between 0.430 inches and 0.440 inches Undercut Width: Between 0.080 inches and 0.090 inches End Application: Nt64 engine Pin Head Diameter: Between 0.180 inches and 0.190 inches Product Name: Pin, straight, d-headed Height: 0.076 inches Material: Steel comp 4140 Material Specification: Ams 6382 assn standard single material response Surface Treatment Specification: Ams 2404 assn standard single treatment response Style Designator: Groove Shelf Life: N/a Unit Of Measure: No | Between 0.092 inches and 0.093 inches |
| Undercut Diameter:Between 0.061 inches and 0.067 inchesUnder Head Length:Between 0.430 inches and 0.440 inchesUndercut Width:Between 0.080 inches and 0.090 inchesEnd Application:Nt64 enginePin Head Diameter:Between 0.180 inches and 0.190 inchesProduct Name:Pin, straight, d-headedHeight:0.076 inchesMaterial:Steel comp 4140Material Specification:Ams 6382 assn standard single material responseSurface Treatment:NickelSurface Treatment Specification:Ams 2404 assn standard single treatment responseSyle Designator:GrooveShelf Life:N/aUnit Of Measure:Pemilitarization:NoFig: | Effective Length: |
| Between 0.061 inches and 0.067 inches Under Head Length: Between 0.430 inches and 0.440 inches Undercut Width: Between 0.080 inches and 0.090 inches End Application: Nt64 engine Pin Head Diameter: Between 0.180 inches and 0.190 inches Product Name: Pin, straight, d-headed Height: 0.076 inches Material: Steel comp 4140 Material Specification: Ams 6382 assn standard single material response Surface Treatment: Nickel Surface Treatment Specification: Ams 2404 assn standard single treatment response Style Designator: Groove Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Between 0.095 inches and 0.105 inches |
| Under Head Length:Between 0.430 inches and 0.440 inchesUndercut Width:Between 0.080 inches and 0.090 inchesEnd Application:Nt64 enginePin Head Diameter:Between 0.180 inches and 0.190 inchesProduct Name:Pin, straight, d-headedHeight:0.076 inchesMaterial:Steel comp 4140Material Specification:Ams 6382 assn standard single material responseSurface TreatmentNickelSurface Treatment Specification:Ams 2404 assn standard single treatment responseStyle Designator:GrooveShelf Life:N/aUnit Of Measure:Demilitarization:NoFig: | Undercut Diameter: |
| Between 0.430 inches and 0.440 inches Undercut Width: Between 0.080 inches and 0.090 inches End Application: Nt64 engine Pin Head Diameter: Between 0.180 inches and 0.190 inches Product Name: Pin, straight, d-headed Height: 0.076 inches Material: Steel comp 4140 Material Specification: Ams 6382 assn standard single material response Surface Treatment Specification: Ams 2404 assn standard single treatment response Style Designator: Groove Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Between 0.061 inches and 0.067 inches |
| Undercut Width:Between 0.080 inches and 0.090 inchesEnd Application:Nt64 enginePin Head Diameter:Between 0.180 inches and 0.190 inchesProduct Name:Pin, straight, d-headedHeight:0.076 inchesMaterial:Steel comp 4140Material Specification:Ams 6382 assn standard single material responseSurface Treatment:NickelSurface Treatment Specification:Ams 2404 assn standard single treatment responseStyle Designator:GrooveShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig: | Under Head Length: |
| Between 0.080 inches and 0.090 inches End Application: Nt64 engine Pin Head Diameter: Between 0.180 inches and 0.190 inches Product Name: Pin, straight, d-headed Height: 0.076 inches Material: Steel comp 4140 Material Specification: Ams 6382 assn standard single material response Surface Treatment: Nickel Surface Treatment Specification: Ams 2404 assn standard single treatment response Style Designator: Groove Shelf Life: N/a Unit Of Measure: Demilitarization: No | Between 0.430 inches and 0.440 inches |
| End Application: Nt64 engine Pin Head Diameter: Between 0.180 inches and 0.190 inches Product Name: Pin, straight, d-headed Height: 0.076 inches Material: 0.076 inches Material: Steel comp 4140 Material Specification: Ams 6382 assn standard single material response Surface Treatment: Nickel Surface Treatment Specification: Ams 2404 assn standard single treatment response Style Designator: Groove Shelf Life: N/a Unit Of Measure: Demilitarization: No | Undercut Width: |
| Nt64 engine Pin Head Diameter: Between 0.180 inches and 0.190 inches Product Name: Pin, straight, d-headed Height: 0.076 inches Material: Steel comp 4140 Material Specification: Ams 6382 assn standard single material response Surface Treatment: Nickel Surface Treatment Specification: Ams 2404 assn standard single treatment response Style Designator: Groove Shelf Life: N/a Unit Of Measure: No No Fiig: | Between 0.080 inches and 0.090 inches |
| Pin Head Diameter: Between 0.180 inches and 0.190 inches Product Name: Pin, straight, d-headed Height: 0.076 inches Material: 0.076 inches Material: Steel comp 4140 Material Specification: Ams 6382 assn standard single material response Surface Treatment: Nickel Surface Treatment Specification: Ams 2404 assn standard single treatment response Style Designator: Groove Shelf Life: N/a Unit Of Measure: Demilitarization: No | End Application: |
| Between 0.180 inches and 0.190 inches Product Name: Pin, straight, d-headed Height: 0.076 inches Material: Steel comp 4140 Material Specification: Ams 6382 assn standard single material response Surface Treatment: Nickel Surface Treatment Specification: Ams 2404 assn standard single treatment response Style Designator: Groove Shelf Life: N/a Unit Of Measure: Demilitarization: No | Nt64 engine |
| Product Name: Pin, straight, d-headed Height: 0.076 inches Material: Steel comp 4140 Material Specification: Ams 6382 assn standard single material response Surface Treatment: Nickel Surface Treatment Specification: Ams 2404 assn standard single treatment response Style Designator: Groove Shelf Life: N/a Unit Of Measure: Demilitarization: No | Pin Head Diameter: |
| Pin, straight, d-headed Height: 0.076 inches Material: Steel comp 4140 Material Specification: Ams 6382 assn standard single material response Surface Treatment: Nickel Surface Treatment Specification: Ams 2404 assn standard single treatment response Style Designator: Groove Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Between 0.180 inches and 0.190 inches |
| Height: 0.076 inches Material: Steel comp 4140 Material Specification: Ams 6382 assn standard single material response Surface Treatment: Nickel Surface Treatment Specification: Ams 2404 assn standard single treatment response Style Designator: Groove Shelf Life: N/a Unit Of Measure: Demilitarization: No | Product Name: |
| 0.076 inches Material: Steel comp 4140 Material Specification: Ams 6382 assn standard single material response Surface Treatment: Nickel Surface Treatment Specification: Ams 2404 assn standard single treatment response Style Designator: Groove Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Pin, straight, d-headed |
| Material: Steel comp 4140 Material Specification: Ams 6382 assn standard single material response Surface Treatment: Nickel Surface Treatment Specification: Ams 2404 assn standard single treatment response Style Designator: Groove Shelf Life: N/a Unit Of Measure: No Fiig: | Height: |
| Steel comp 4140 Material Specification: Ams 6382 assn standard single material response Surface Treatment: Nickel Surface Treatment Specification: Ams 2404 assn standard single treatment response Style Designator: Groove Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | 0.076 inches |
| Material Specification: Ams 6382 assn standard single material response Surface Treatment: Nickel Surface Treatment Specification: Ams 2404 assn standard single treatment response Style Designator: Groove Shelf Life: N/a Unit Of Measure: Demilitarization: No | Material: |
| Ams 6382 assn standard single material response Surface Treatment: Nickel Surface Treatment Specification: Ams 2404 assn standard single treatment response Style Designator: Groove Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Steel comp 4140 |
| Surface Treatment: Nickel Surface Treatment Specification: Ams 2404 assn standard single treatment response Style Designator: Groove Shelf Life: N/a Unit Of Measure: Demilitarization: No | Material Specification: |
| Nickel Surface Treatment Specification: Ams 2404 assn standard single treatment response Style Designator: Groove Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Ams 6382 assn standard single material response |
| Surface Treatment Specification: Ams 2404 assn standard single treatment response Style Designator: Groove Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Surface Treatment: |
| Ams 2404 assn standard single treatment response Style Designator: Groove Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Nickel |
| Style Designator: Groove Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Surface Treatment Specification: |
| Groove Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Ams 2404 assn standard single treatment response |
| Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Style Designator: |
| N/a Unit Of Measure: Demilitarization: No Fiig: | Groove |
| Unit Of Measure: Demilitarization: No Fiig: | Shelf Life: |
| Demilitarization: No Fiig: | N/a |
| Demilitarization: No Fiig: | Unit Of Measure: |
| No Fiig: | |
| Fiig: | Demilitarization: |
| - | No |
| A212a0 | Fiig: |
| | A212a0 |
| | |