## NSN 5315-01-601-2430

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-601-2430 **Shank Diameter:** Between 0.2470 inches and 0.2495 inches **Detent Quantity:** 2 **Actuation Method:** Push button **Grip Length:** Between 1.100 inches and 1.120 inches **Actuation Type:** Push **Hardness Rating:** 36.0 rockwell c shank and 40.0 rockwell c shank **Shear Strength:** 8200 double pound **Shoulder To Head End Distance:** 1.550 inches Pin Center To Handle End Distance: 1.780 inches Pin Attachment Type: Ring **Detent To Tapered End Distance:** 0.380 inches Material: Steel comp 4130 spindle **Material Specification:** Mil-s-6758 military specification single material response spindle **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Style Designator:** L handle **Specification Data:** 80205-nas1334 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No Fiig:

A212a0

## NSN 5315-01-601-2430

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.