NSN 5315-01-603-0153

Headless Grooved Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-603-0153

| First End Styles |
|--|
| First End Style: Chamfered |
| |
| Second End Style: |
| |
| Overall Length: |
| Between 1.071 inches and 1.072 inches |
| Diameter: Between 0.243 inches and 0.245 inches |
| Effective Length: |
| Between 1.012 inches and 1.013 inches |
| Undercut Diameter: |
| Between 0.227 inches and 0.231 inches |
| Undercut Width: |
| Between 0.030 inches and 0.033 inches |
| Second Undercut Width: |
| Between 0.030 inches and 0.033 inches |
| Undercut Radius: |
| 0.003 inches |
| End Application: |
| 2320-01-534-1091; cargo truck |
| First End Taper Length: |
| 0.010 inches |
| Second End Taper Length: |
| 0.010 inches |
| Second End Relationship With First End: |
| Identical |
| First End Location: |
| Both ends |
| First End Taper Angle: |
| 45.0 degrees |
| Second End Taper Angle: |
| 45.0 degrees |
| Product Name: |
| Roller shaft |
| Material: |
| Steel comp 303 |
| Material Specification: |
| Astm a581 assn standard single material response or 582 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Sae-ams 2700 assn standard single treatment response |

NSN 5315-01-603-0153

Headless Grooved Pin - Page 2 of 2

Style Designator:

Groove

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A212a0

