

View Online at <https://aerobasegroup.com/nsn/5315-01-603-2832>

Shank Diameter:

Between 0.3095 inches and 0.3110 inches

Detent Quantity:

4

Actuation Method:

Push button

Grip Length:

1.000 inches

Actuation Type:

Pull and push

Hardness Rating:

58.0 rockwell c and 62.0 rockwell c detent

Shear Strength:

14400 double pounds per square inch

Shoulder To Head End Distance:

1.580 inches

Pin Center To Handle End Distance:

0.740 inches

Pin Attachment Type:

Ring

Detent To Tapered End Distance:

0.400 inches

Material:

Steel comp 631 or steel comp 302 spring

Material Specification:

Astm b85 assn standard single material response or qq-a-225/3 federal specification single material response or qq-a-225/5 federal specification single material response or qq-a-225/6 federal specification single material response or astm b221 assn standard single material response or qq-a-200/8 federal specification single material response or qq-a-225/8 federal specification single material response or astm a582 assn standard single material response or astm a484/a581 assn standard single material response or ams 5640 assn standard single material response or qq-a-225/9 federal specification single material response handle

Surface Treatment:

Passivate

Style Designator:

L handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-b-1083 spec.