

View Online at <https://aerobasegroup.com/nsn/5315-01-603-2832>

**Shank Diameter:**

Between 0.3095 inches and 0.3110 inches

**Detent Quantity:**

4

**Actuation Method:**

Push button

**Grip Length:**

1.000 inches

**Actuation Type:**

Pull and push

**Hardness Rating:**

58.0 rockwell c and 62.0 rockwell c detent

**Shear Strength:**

14400 double pounds per square inch

**Shoulder To Head End Distance:**

1.580 inches

**Pin Center To Handle End Distance:**

0.740 inches

**Pin Attachment Type:**

Ring

**Detent To Tapered End Distance:**

0.400 inches

**Material:**

Steel comp 631 or steel comp 302 spring

**Material Specification:**

Astm b85 assn standard single material response or qq-a-225/3 federal specification single material response or qq-a-225/5 federal specification single material response or qq-a-225/6 federal specification single material response or astm b221 assn standard single material response or qq-a-200/8 federal specification single material response or qq-a-225/8 federal specification single material response or astm a582 assn standard single material response or astm a484/a581 assn standard single material response or ams 5640 assn standard single material response or qq-a-225/9 federal specification single material response handle

**Surface Treatment:**

Passivate

**Style Designator:**

L handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-b-1083 spec.