

View Online at <https://aerobasegroup.com/nsn/5315-01-604-1145>

Head Diameter:

0.750 inches

Handle Length:

Between 1.750 inches and 2.000 inches

Shank Diameter:

Between 0.3095 inches and 0.3110 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

3.300 inches

Actuation Type:

Pull and push

Hardness Rating:

58.0 rockwell c and 62.0 rockwell c detent

Shear Strength:

14400 double pound

Shoulder To Head End Distance:

1.580 inches

Detent To Tapered End Distance:

0.400 inches

Material:

Steel comp 630 or steel comp xm-12 or steel comp 632 or steel comp 631 shank

Material Specification:

Astm b85 assn standard single material response or qq-a-225/3 federal specification single material response or qq-a-225/5 federal specification single material response or qq-a-225/6 federal specification single material response or astm b221 assn standard single material response or qq-a-200/8 federal specification single material response or qq-a-225/8 federal specification single material response or qq-a-225/9 federal specification single material response head

Surface Treatment:

Passivate spring

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response handle

Style Designator:

T handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-b-1083 spec