## NSN 5315-01-604-7238

Headless Shoulder Pin - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5315-01-604-7238



First End Style: Square **Second End Style:** Chamfered **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.405 inches **Shank Length:** 0.903 inches **Shoulder Width Across Flats:** Between 0.615 inches and 0.627 inches **Shank Diameter:** Between 0.374 inches and 0.375 inches **Overall Length:** 1.433 inches **End Application:** Fwd fuse 45 **Second End Taper Length:** Between 0.321 inches and 0.361 inches **Second End Relationship With First End:** Not identical **Thread Size:** 0.375 inches **Second Shank Diameter:** Between 0.3740 inches and 0.3745 inches First End Location: Threaded end First End Tip Radius: Between 0.060 inches and 0.090 inches **Second End Tip Radius:** Between 0.060 inches and 0.090 inches **Second End Taper Angle:** 45.0 degrees **Second Shank Length:** 0.562 inches **Product Name:** Pin-index Material: Steel comp 302 or steel comp 304 or steel comp 303se

## NSN 5315-01-604-7238

Headless Shoulder Pin - Page 2 of 2



Surface Treatment:
Passivate
Style Designator:
Shoulder
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A212a0