

View Online at <https://aerobasegroup.com/nsn/5315-01-607-7933>

First End Style:

Chamfered and countersunk

Head Style:

Flat chamfer

Under Head Length:

Between 1.2675 inches and 1.2875 inches

First Step Diameter:

Between 0.3896 inches and 0.3901 inches

First Step Length:

Between 0.6825 inches and 0.6925 inches

Second Step Diameter:

Between 0.3640 inches and 0.3680 inches

Second Step Length:

0.590 inches

End Application:

F/a-18 e/f

First End Taper Length:

0.030 inches

Shear Strength:

30000 double pounds per square inch

First End Taper Angle:

Between 0.215 degrees and 0.235 degrees

Pin Head Diameter:

Between 0.565 inches and 0.600 inches

First End Countersink Angle:

Between 90.0 degrees and 100.0 degrees

First End Countersink Diameter:

Between 0.197 inches and 0.217 inches

Product Name:

Pin-rivet, threaded, tension

Height:

Between 0.130 inches and 0.140 inches

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Shoulder

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A212a0