

View Online at <https://aerobasegroup.com/nsn/5315-01-611-1142>

First End Style:

Chamfered

Head Length:

Between 0.746 inches and 0.748 inches

Under Head Length:

2.880 inches

First Step Diameter:

0.563 inches

First Step Length:

0.688 inches

Second Step Diameter:

Between 0.498 inches and 0.500 inches

Second Step Length:

1.442 inches

Third Step Diameter:

Between 0.335 inches and 0.345 inches

Third Step Length:

0.750 inches

Head Width:

Between 0.746 inches and 0.748 inches

End Application:

Howitzer, 155mm, m777e1

First End Taper Length:

0.030 inches

Hardness Rating:

42.0 rockwell c and 44.0 rockwell c

First End Taper Angle:

45.0 degrees

Product Name:

Pin, frame lock

Special Features:

Hardness depends on steel material used: steel 4130 rockwell hardness c 42-44 and steel 4140 rockwell hardness c 40-42

Height:

1.750 inches

Material:

Steel comp 4130 or steel comp 4140

Material Specification:

Astm a322 assn standard single material response

Style Designator:

Shoulder

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A212a0