

View Online at <https://aerobasegroup.com/nsn/5315-01-615-9289>

Shank Diameter:

Between 0.2485 inches and 0.2500 inches

Detent Quantity:

2

Lanyard Length:

Between 5.50 inches and 6.50 inches

End Application:

5895-01-556-1797

Grip Length:

Between 2.100 inches and 2.120 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c spindle

Shoulder To Head End Distance:

1.270 inches

Pin Center To Handle End Distance:

1.38 inches

Pin Attachment Type:

Cable lanyard w/terminations

Detent To Tapered End Distance:

Between 0.260 inches and 0.290 inches

Product Name:

Pin, quick release

Special Features:

Cable size 1/16 diameter. 7 x 7 corrosion resistant steel per mil-w-8342; vinyl coated - color green; per mil-i-631. Rated full strength; 480 lbs; swaging sleeve; nicopress 28-ic or equiv

Material:

Stainless steel spindle

Material Specification:

Astm b85 assn standard single material response handle

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Qq-p-416 type i or type ii class 2 assn standard single treatment response handle

Style Designator:

L handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0