

View Online at <https://aerobasegroup.com/nsn/5315-01-626-5959>

First End Style:

Chamfered w/thru hole

Second End Style:

Radius

Pinlength:

31.75 millimeters

Pindiameter:

9.52 millimeters

End Application:

Model aslav, 715591

Second End Corner Radius:

Between 1.19 millimeters and 3.17 millimeters

First End Taper Length:

23.81 millimeters

Second End Relationship With First End:

Not identical

Hardness Rating:

36.0 rockwell c and 42.0 rockwell c

Shear Strength:

16000 double pounds per square inch

First End Taper Angle:

Between 4.0 degrees and 16.0 degrees

Surface Finish:

16.0 microinches chamfered end

Product Name:

Pin, latch

Special Features:

Item has one 1.6 mm diameter hole drilled through the entire lgt, another 1.6 mm diameter hole drilled 19.05 mm from chamfered end, a second hole drilled 27.77 mm from chamfered end is 3.15/3.27 mm dia; item is made from ms16555-660 specification

Material:

Steel comp 416 or steel comp 410

Material Specification:

Astm a582 or astm a483 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Astm a380 assn standard single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0