NSN 5315-01-627-0270

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-627-0270

First End Style:

Second End Style:
Chamfered
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.405 inches
Shank Length:
0.593 inches
Shoulder Width Across Flats:
Between 0.430 inches and 0.439 inches
Shank Diameter:
Between 0.1890 inches and 0.1895 inches
Overall Length:
1.713 inches
End Application:
F-15sa
First End Taper Length:
0.030 inches
Second End Taper Length:
0.120 inches
Thready Qty Per Inch (tpi):
28
Second End Relationship With First End:
Not identical
1 tot labilitioal
Thread Size:
Thread Size:
Thread Size: 0.2500 inches
Thread Size: 0.2500 inches Second Shank Diameter:
Thread Size: 0.2500 inches Second Shank Diameter: Between 0.2490 inches and 0.2495 inches
Thread Size: 0.2500 inches Second Shank Diameter: Between 0.2490 inches and 0.2495 inches First End Location:
Thread Size: 0.2500 inches Second Shank Diameter: Between 0.2490 inches and 0.2495 inches First End Location: Threaded end
Thread Size: 0.2500 inches Second Shank Diameter: Between 0.2490 inches and 0.2495 inches First End Location: Threaded end First End Taper Angle:
Thread Size: 0.2500 inches Second Shank Diameter: Between 0.2490 inches and 0.2495 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees
Thread Size: 0.2500 inches Second Shank Diameter: Between 0.2490 inches and 0.2495 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees Second End Tip Radius:
Thread Size: 0.2500 inches Second Shank Diameter: Between 0.2490 inches and 0.2495 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees Second End Tip Radius: Between 0.060 inches and 0.090 inches
Thread Size: 0.2500 inches Second Shank Diameter: Between 0.2490 inches and 0.2495 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees Second End Tip Radius: Between 0.060 inches and 0.090 inches Second Shank Length:

NSN 5315-01-627-0270

Headless Shoulder Pin - Page 2 of 2

Fiig: A212a0



Material:
Steel comp 302 or steel comp 303se or steel comp 304
Material Specification:
Qq-s-763 federal standard single material response or mms 265 mfr ref single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal standard single treatment response
Style Designator:
Shoulder
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No