NSN 5315-01-632-3229

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-632-3229 First End Style: Chamfered Second End Style: Oval **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.405 inches **Shank Length:** 0.655 inches **Shoulder Diameter:** Between 0.430 inches and 0.439 inches **Shoulder Width Across Flats:** Between 0.430 inches and 0.439 inches **Shank Diameter:** 0.250 inches **Overall Length:** 1.280 inches **Hole Arrangement Style:** One end drilled First Hole Diameter: Between 0.076 inches and 0.086 inches **Distance From Centerline Of Hole To End Of Pin:** 0.140 inches First End Taper Length: 0.030 inches Thready Qty Per Inch (tpi): 28 Second End Relationship With First End: Not identical **Thread Size:** 0.250 inches **Second Shank Diameter:** Between 0.3120 inches and 0.3125 inches **First End Location:** Chamfered end First End Taper Angle: 45.0 degrees **Second End Outer Radius:**

Between 0.060 inches and 0.090 inches

NSN 5315-01-632-3229

Headless Shoulder Pin - Page 2 of 2



Second Shank Length:
1.405 inches
Material:
Stainless steel
Material Specification:
Ph13-8-0 mfr ref single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Astm 2700, method 1 assn standard single treatment response
Style Designator:
Shoulder
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A212a0