

View Online at <https://aerobasegroup.com/nsn/5315-01-656-7415>

Head Diameter:

Between 2.220 inches and 2.345 inches

Shoulder Diameter:

Between 0.630 inches and 0.800 inches

Shank Diameter:

Between 0.4970 inches and 0.4985 inches

Ring Handle Diameter:

0.100 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 4.30 inches and 4.32 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c spindle

Shoulder To Head End Distance:

0.885 inches

Pin Attachment Type:

Ring or hook

Detent To Tapered End Distance:

Between 0.420 inches and 0.460 inches

Product Name:

Pin, quick release, self-retaining, positive locking, single acting, "t" handle

Material:

Steel comp 630 or steel comp 632 spindle

Material Specification:

Astm a484/a484m, astm a581/a581m or astm a582/a582m assn standard single material response button

Surface Treatment:

Passivate

Surface Treatment Specification:

Ams2700, method 1, class 4 national std/spec single treatment response

Style Designator:

Ring handle

Specification Data:

80205-nas-17985 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0