

View Online at <https://aerobasegroup.com/nsn/5315-01-656-7415>

**Head Diameter:**

Between 2.220 inches and 2.345 inches

**Shoulder Diameter:**

Between 0.630 inches and 0.800 inches

**Shank Diameter:**

Between 0.4970 inches and 0.4985 inches

**Ring Handle Diameter:**

0.100 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 4.30 inches and 4.32 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c spindle

**Shoulder To Head End Distance:**

0.885 inches

**Pin Attachment Type:**

Ring or hook

**Detent To Tapered End Distance:**

Between 0.420 inches and 0.460 inches

**Product Name:**

Pin, quick release, self-retaining, positive locking, single acting, "t" handle

**Material:**

Steel comp 630 or steel comp 632 spindle

**Material Specification:**

Astm a484/a484m, astm a581/a581m or astm a582/a582m assn standard single material response button

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Ams2700, method 1, class 4 national std/spec single treatment response

**Style Designator:**

Ring handle

**Specification Data:**

80205-nas-17985 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0