## NSN 5320-00-001-5178

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-001-5178 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.842 inches and 0.862 inches **Head Style:** Flush countersunk Width Between Flats: 0.094 inches **Shank Diameter:** Between 0.263 inches and 0.265 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.507 inches **Grip Length:** Between 0.751 inches and 0.812 inches Thready Qty Per Inch (tpi): 48 Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.216 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** Hex socket in head Material: Steel comp 8740 **Material Specification:** Aisi assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Uns Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5320-00-001-5178

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0