

View Online at <https://aerobasegroup.com/nsn/5320-00-003-8012>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.1140 inches and 1.1340 inches

Head Style:

Err-090

Head Height:

Between 0.0550 inches and 0.0600 inches

Width Between Flats:

0.0780 inches

Shank Diameter:

Between 0.1615 inches and 0.1635 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.3060 inches and 0.3220 inches

Grip Length:

Between 0.8070 inches and 0.8170 inches

Features Provided:

Washer

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.1640 inches

Material:

Steel comp 4130 bolt or steel comp 4140 bolt or steel comp 8740 bolt

Material Specification:

Mil-s-7720 military specification single material response collar or qq-s-763 federal specification single material response collar

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-s-763 federal specification single treatment response collar

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6758 spec.