

View Online at <https://aerobasegroup.com/nsn/5320-00-005-6253>

**Fastener Length:**

0.287 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.186 inches and 0.190 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.186 inches and 0.190 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.080 inches and 0.125 inches

**Shear Strength:**

710 single pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Heat Treatment:**

H-38 strain hardened locking ring

**Material:**

Aluminum alloy 5056 locking ring

**Material Specification:**

Qq-a-430 federal specification single material response locking ring

**Surface Treatment:**

Anodize sleeve or chromate sleeve

**Surface Treatment Specification:**

Mil-c-5541, cl 1a military specification single treatment response stem

**Specification Data:**

80205-nas1399 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.