

View Online at <https://aerobasegroup.com/nsn/5320-00-005-6256>

**Fastener Length:**

0.328 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

0.094 inches

**Shank Style:**

Pull through hollow shank

**Head Major Diameter:**

0.090 inches

**Expansion Device:**

Serrated stem-type w

**End Application:**

W/s: ticonderoga class cg (47); spruance class dd (963); helicopter, hh-53h pace low; engine, aircraft, tf39-ge-1 (c-5a); helicopter, advance attack, ah-1w; engine, aircraft, tf-33-p-7 (c-141a/b); aircraft, (ac-130h, mc-130h, ec-130e, hc-130); engine, aircraft, tf33-p-3/5/9 (c/ec-135, b-52h); engine, aircraft, tf33-pw-102 (c-135e, ec-135h/k/p); hh-60l medivac

**Grip Length:**

Between 0.188 inches and 0.250 inches

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0