NSN 5320-00-006-0798

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-006-0798

Fastener Length:

0.350 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.124 inches and 0.128 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.221 inches and 0.229 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.126 inches and 0.187 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Sleeve orange color no. 32246 federal standard 595

Heat Treatment:

H-38 strain hardened locking ring

Material:

Aluminum alloy 5056 locking ring

Material Specification:

Qq-a-430 federal specification single material response locking ring

Surface Treatment:

Anodize stem or chromate stem

Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response stem or mil-c-5541 military specification 2nd treatment response stem

Specification Data:

80205-nas1399 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.