## NSN 5320-00-006-2580



Blind Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-00-006-2580 Fastener Length: 0.510 inches **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.249 inches and 0.253 inches **Shank Style:** Self-plugging mechanically locked stem **Head Major Diameter:** Between 0.472 inches and 0.480 inches **Expansion Device:** Serrated stem-type w **Grip Length:** Between 0.251 inches and 0.312 inches **Shear Strength:** 1610 single pounds per square inch **Countersink Angle:** 100.0 degrees **Heat Treatment:** H-38 strain hardened locking ring Material: Aluminum alloy 5056 locking ring **Material Specification:** Qq-a-430 federal specification single material response stem **Surface Treatment:** Anodize or chromate **Surface Treatment Specification:** Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response **Specification Data:** 80205-nas1399 professional/industrial association standard Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.