

View Online at <https://aerobasegroup.com/nsn/5320-00-007-0359>

Fastener Length:

0.475 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.186 inches and 0.190 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.349 inches and 0.357 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.251 inches and 0.312 inches

Shear Strength:

820 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Self-locking

Heat Treatment:

H-38 strain hardened locking ring

Material:

Aluminum alloy 5056 locking ring

Material Specification:

Qq-a-430 federal specification single material response locking ring

Surface Treatment:

Anodize or chromate

Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

Specification Data:

80205-nas1399 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.