NSN 5320-00-012-1650

Tubular Rivet - Page 1 of 1

Fiig: A040a0



View Online at https://aerobasegroup.com/nsn/5320-00-012-1650 **Fastener Length:** Between 0.678 inches and 0.698 inches **Head Style:** Oval/truss **Head Height:** Between 0.055 inches and 0.065 inches **Hole Diameter:** Between 0.133 inches and 0.139 inches **Shank Diameter:** Between 0.182 inches and 0.188 inches **Shank Style:** Tubular **Head Major Diameter:** Between 0.306 inches and 0.318 inches **Hole Depth:** Between 0.141 inches and 0.172 inches **Shear Strength:** 36000 double pounds per square inch Material: Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 **Material Specification:** 66 federal standard all material responses **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response Shelf Life: N/a **Unit Of Measure: Demilitarization:** No