NSN 5320-00-012-1650

Tubular Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-012-1650

Fastener Length:

Between 0.678 inches and 0.698 inches

Head Style:

Oval/truss

Head Height:

Between 0.055 inches and 0.065 inches

Hole Diameter:

Between 0.133 inches and 0.139 inches

Shank Diameter:

Between 0.182 inches and 0.188 inches

Shank Style:

Tubular

Head Major Diameter:

Between 0.306 inches and 0.318 inches

Hole Depth:

Between 0.141 inches and 0.172 inches

Shear Strength:

36000 double pounds per square inch

Material:

Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp

1020 or steel comp 1021 or steel comp 1022

Material Specification:

66 federal standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

```
--
```

Demilitarization:

No

Fiig:

A040a0