

View Online at <https://aerobasegroup.com/nsn/5320-00-012-2292>

**Fastener Length:**

Between 0.340 inches and 0.370 inches

**Head Style:**

Hexagon

**Head Height:**

0.096 inches

**Shank Diameter:**

Between 0.1625 inches and 0.1645 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Expansion Device:**

Threaded stem

**Lubrication:**

Wax or dry film

**Grip Length:**

Between 0.220 inches and 0.281 inches

**Width Across Flats:**

Between 0.277 inches and 0.283 inches

**Shear Strength:**

1920 double pounds per square inch

**Material:**

Steel comp 304 sleeve or steel comp 303f sleeve

**Material Specification:**

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or ams5641 assn standard 2nd material response sleeve or astm a582, type 303 assn standard 3rd material response sleeve

**Surface Treatment:**

Passivate sleeve and cadmium sleeve

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response bolt

**Specification Data:**

80205-nas1673 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-5626 spec.