

View Online at <https://aerobasegroup.com/nsn/5320-00-012-2292>

Fastener Length:

Between 0.340 inches and 0.370 inches

Head Style:

Hexagon

Head Height:

0.096 inches

Shank Diameter:

Between 0.1625 inches and 0.1645 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Threaded stem

Lubrication:

Wax or dry film

Grip Length:

Between 0.220 inches and 0.281 inches

Width Across Flats:

Between 0.277 inches and 0.283 inches

Shear Strength:

1920 double pounds per square inch

Material:

Steel comp 304 sleeve or steel comp 303f sleeve

Material Specification:

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or ams5641 assn standard 2nd material response sleeve or astm a582, type 303 assn standard 3rd material response sleeve

Surface Treatment:

Passivate sleeve and cadmium sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response bolt

Specification Data:

80205-nas1673 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.