NSN 5320-00-013-6539

Tubular Rivet - Page 1 of 1



3-6539

,	View Online at https://aerobasegroup.com/nsn/5320-00-013
	Fastener Length:
	Between 0.334 inches and 0.354 inches
ı	Head Style:
(Countersunk w/ reverse chamfer
	Head Height:
ı	Between 0.055 inches and 0.065 inches
-	Hole Diameter:
-	Between 0.133 inches and 0.139 inches
;	Shank Diameter:
-	Between 0.182 inches and 0.188 inches
;	Shank Style:
	Tubular
-	Head Major Diameter:
-	Between 0.351 inches and 0.367 inches
-	Hole Depth:
ı	Between 0.141 inches and 0.172 inches
,	Shear Strength:
;	36000 double pounds per square inch
(Countersink Angle:
	Between 148.0 degrees and 150.0 degrees
	Material:
(Copper alloy 260 or copper alloy 270
	Material Specification:
(Qq-w-321 federal specification all material responses
;	Surface Treatment:
(Oxide
į	Surface Treatment Specification:
	Mil-f-495 military specification single treatment response
,	Shelf Life:
	N/a
	Unit Of Measure:
ı	Demilitarization:
	No
ı	Fiig:

A040a0

Mil-std (military Standard):

Mil-f-495 spec.