NSN 5320-00-013-7948

Tubular Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-013-7948

| Fastener Length: |
|---|
| Between 0.178 inches and 0.198 inches |
| Head Style: |
| Oval/truss |
| Hole Diameter: |
| Between 0.099 inches and 0.104 inches |
| Shank Diameter: |
| Between 0.141 inches and 0.146 inches |
| Shank Style: |
| Tubular |
| Hole Depth: |
| Between 0.109 inches and 0.141 inches |
| End Application: |
| W/s: support equipment, f-5 aircraft |
| Shear Strength: |
| 36000 double pounds per square inch |
| Material: |
| Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1012 |
| or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp |
| 1020 or steel comp 1021 or steel comp 1022 |
| Material Specification: |
| 66 federal standard all material responses |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, type 2, class 2 federal specification single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| |
| |
| |