## NSN 5320-00-013-7948

Tubular Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-013-7948

Fastener Length:
Between 0.178 inches and 0.198 inches
Head Style:
Oval/truss
Hole Diameter:
Between 0.099 inches and 0.104 inches
Shank Diameter:
Between 0.141 inches and 0.146 inches
Shank Style:
Tubular
Hole Depth:
Between 0.109 inches and 0.141 inches
End Application:
W/s: support equipment, f-5 aircraft
Shear Strength:
36000 double pounds per square inch
Material:
Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1012
or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp
1020 or steel comp 1021 or steel comp 1022
Material Specification:
66 federal standard all material responses
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification single treatment response
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A040a0