

View Online at <https://aerobasegroup.com/nsn/5320-00-017-4950>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.582 inches and 0.602 inches

**Head Height:**

Between 0.037 inches and 0.047 inches

**Width Between Flats:**

Between 0.079 inches and 0.080 inches

**Shank Diameter:**

Between 0.163 inches and 0.164 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.242 inches and 0.262 inches

**Grip Length:**

0.317 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

260000 pounds per square inch

**Hardness Rating:**

50.0 rockwell c and 55.0 rockwell c

**Thread Size:**

0.164 inches

**Shear Strength:**

156000 single pounds per square inch

**Special Features:**

Head style flat chamfer

**Material:**

Steel comp h11

**Material Specification:**

Ams 6485 assn standard single material response

**Surface Treatment:**

Cadmium or nickel and cadmium

**Surface Treatment Specification:**

Mil-c-8837, type 2, cl 2 military specification 1st treatment response or ams 2416 assn standard 2nd treatment response or ams 2416 assn standard 3rd treatment response

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-c-8837 spec.