# NSN 5320-00-034-5269

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-034-5269



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.185 inches and 1.205 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.059 inches and 0.069 inches

#### Width Between Flats:

Between 0.095 inches and 0.097 inches

#### Shank Diameter:

Between 0.2485 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.387 inches and 0.412 inches

# Grip Length:

0.880 inches

# Hardness Rating:

50.0 rockwell c and 55.0 rockwell c

# Thread Size:

0.250 inches

#### Shear Strength:

156000 single pounds per square inch

#### Material:

Steel comp h11

#### **Material Specification:**

Ams 6485 assn standard single material response

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Mil-c-8837, type 2, cl 2 military specification single treatment response

#### Thread Series Designator:

Unjf

# Shelf Life:

N/a

### Unit Of Measure:

--

### Demilitarization:

No

# NSN 5320-00-034-5269

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

Mil-std (military Standard):

Mil-c-8837 spec.

