

View Online at <https://aerobasegroup.com/nsn/5320-00-043-1992>

**Fastener Length:**

Between 1.088 inches and 1.118 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.100 inches and 0.116 inches

**Shank Diameter:**

Between 0.194 inches and 0.199 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Expansion Device:**

Threaded stem

**Lubrication:**

Cetyl alcohol or dry film or solid film

**Grip Length:**

1.000 inches

**Width Across Flats:**

Between 0.302 inches and 0.312 inches

**Min. Tensile Strength (psi):**

1100 pounds per square inch

**Shear Strength:**

5240 double pounds per square inch

**Material:**

Steel

**Material Specification:**

Ams 5636 assn standard single material response or ams 5639 assn standard single material response or ams 5641 assn standard single material response sleeve

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification single treatment response or nas 672 assn standard single treatment response or qq-p-416, type 1, class 3 federal specification single treatment response stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6049 spec.