

View Online at <https://aerobasegroup.com/nsn/5320-00-043-1992>

Fastener Length:

Between 1.088 inches and 1.118 inches

Head Style:

Hexagon

Head Height:

Between 0.100 inches and 0.116 inches

Shank Diameter:

Between 0.194 inches and 0.199 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Threaded stem

Lubrication:

Cetyl alcohol or dry film or solid film

Grip Length:

1.000 inches

Width Across Flats:

Between 0.302 inches and 0.312 inches

Min. Tensile Strength (psi):

1100 pounds per square inch

Shear Strength:

5240 double pounds per square inch

Material:

Steel

Material Specification:

Ams 5636 assn standard single material response or ams 5639 assn standard single material response or ams 5641 assn standard single material response sleeve

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response or nas 672 assn standard single treatment response or qq-p-416, type 1, class 3 federal specification single treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6049 spec.