# NSN 5320-00-045-1818

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-045-1818

## Fastener Length:

Between 0.490 inches and 0.510 inches

#### Head Style:

Undersized oval countersunk

# Head Height:

Between 0.003 inches and 0.005 inches

## Shank Diameter:

Between 0.124 inches and 0.127 inches

#### Shank Style:

Straight w/radius chamfered tip

#### Head Major Diameter:

0.1957 inches

#### Head Minor Diameter:

0.134 mils and 0.144 centimeters

#### **Countersink Height:**

0.0286 inches

# Shear Strength:

26000 single pounds per square inch

#### **Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

#### Heat Treatment:

T-4 solution heat treated

## Material:

Aluminum alloy 2117

#### **Material Specification:**

Qq-a-430 federal specification single material response

#### Surface Treatment:

Anodize or chromate

#### Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

#### **Specification Data:**

80205-nas1097 professional/industrial association standard

#### Shelf Life:

N/a

# Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A040a0

## Mil-std (military Standard):

Mil-a-8625 spec.