
## NSN 5320-00-047-4524

Pin-rivet - Page 1 of 2





**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 1.865 inches and 1.885 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.102 inches and 0.112 inches

#### Width Between Flats:

Between 0.095 inches and 0.097 inches

#### Shank Diameter:

Between 0.3115 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.475 inches and 0.505 inches

#### Lubrication:

Cetyl alcohol

## Grip Length:

1.380 inches

#### Thready Qty Per Inch (tpi):

24

## Thread Size:

0.312 inches

## Shear Strength:

125000 single pounds per square inch

## Material:

Steel comp 431

## Surface Treatment:

Passivate

## Surface Treatment Specification:

258, fscm 73197 mfr ref single treatment response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5320-00-047-4524

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

