## NSN 5320-00-052-3969

Tubular Rivet - Page 1 of 1

A040a0



View Online at https://aerobasegroup.com/nsn/5320-00-052-3969

Fastener Length:
Between 0.245 inches and 0.255 inches
Head Style:
Oval/truss
Head Height:
Between 0.104 inches and 0.114 inches
Hole Diameter:
Between 0.039 inches and 0.043 inches
Shank Diameter:
Between 0.058 inches and 0.061 inches
Shank Style:
Tubular
Head Major Diameter:
Between 0.015 inches and 0.019 inches
Hole Depth:
Between 0.031 inches and 0.062 inches
Features Provided:
Casehardened
Shear Strength:
32000 double pounds per square inch
Material:
Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1012
or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp
1020 or steel comp 1021 or steel comp 1022
Material Specification:
66 federal standard all material responses or aisi/sae assn standard all material responses
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Specification Or Standard:
12 type and e grade and 3 class
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: