

View Online at <https://aerobasegroup.com/nsn/5320-00-052-3969>

Fastener Length:

Between 0.245 inches and 0.255 inches

Head Style:

Oval/truss

Head Height:

Between 0.104 inches and 0.114 inches

Hole Diameter:

Between 0.039 inches and 0.043 inches

Shank Diameter:

Between 0.058 inches and 0.061 inches

Shank Style:

Tubular

Head Major Diameter:

Between 0.015 inches and 0.019 inches

Hole Depth:

Between 0.031 inches and 0.062 inches

Features Provided:

Casehardened

Shear Strength:

32000 double pounds per square inch

Material:

Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022

Material Specification:

66 federal standard all material responses or aisi/sae assn standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Specification Or Standard:

12 type and e grade and 3 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0