
# NSN 5320-00-055-4095

Pin-rivet - Page 1 of 1



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.565 inches and 0.585 inches

## Head Style:

Err-090

#### Head Height:

Between 0.045 inches and 0.055 inches

## Width Between Flats:

Between 0.079 inches and 0.081 inches

## Shank Diameter:

Between 0.202 inches and 0.203 inches

#### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.295 inches and 0.315 inches

## Grip Length:

0.255 inches

# Thread Size:

0.190 inches

## Material:

Steel comp 4140 or steel comp 8740 or steel comp 4130

## **Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6758 military specification 3rd material response

Surface Treatment:

Cadmium

# Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response

## Thread Series Designator:

Unjf

#### Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

## Fiig:

A528u0

## Mil-std (military Standard):

Mil-s-5626 spec.

