

View Online at <https://aerobasegroup.com/nsn/5320-00-058-1748>

**Head Style:**

Flush countersunk

**Shank Diameter:**

Between 0.154 inches and 0.156 inches

**Shank Style:**

Err-090

**Head Major Diameter:**

0.220 inches

**Grip Length:**

Between 0.189 inches and 0.250 inches

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 8735 or steel comp 6150 or steel comp 4140 or steel comp e4340 or steel comp 4340 or steel comp 4037 or steel comp 4130 or steel comp 316 or steel

**Material Specification:**

Mil-s-6098 military specification 1st material response or mil-s-8503 military specification 2nd material response or mil-s-5626 military specification 3rd material response or mil-s-5000 military specification 4th material response or mil-s-5000 military specification 5th material response or mil-s-8695 military specification all material responses or mil-s-6758 military specification 6th material response or qq-s-763, cond a federal specification 7th material response or ams 6330 assn standard 8th material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6098 spec.