

View Online at <https://aerobasegroup.com/nsn/5320-00-058-1750>

Head Style:

Flush countersunk

Shank Diameter:

Between 0.154 inches and 0.156 inches

Shank Style:

Head Major Diameter:

0.220 inches

Grip Length:

Between 0.313 inches and 0.375 inches

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 8735 or steel comp 8740 or steel comp 6150 or steel or steel comp 4140 or steel comp e4340 or steel comp 4340 or steel comp 4037 or steel comp 4130

Material Specification:

Mil-s-6098 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-8503 military specification 3rd material response or ams 6330 assn standard 4th material response or mil-s-5626 military specification 5th material response or mil-s-5000 military specification all material responses or mil-s-5000 military specification 6th material response or mil-s-8695 military specification 7th material response or mil-s-6758 military specification 8th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Specification Data:

80205-nas1055 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6098 spec.