## NSN 5320-00-058-2300

Blind Rivet - Page 1 of 1

Mil-std (military Standard):

Mil-s-5626 spec.



View Online at https://aerobasegroup.com/nsn/5320-00-058-2300 **Head Style:** Hexagon **Head Height:** 0.160 inches **Shank Diameter:** Between 0.3095 inches and 0.3115 inches **Shank Style:** Threaded self-plugging shank w/sleeve **Expansion Device:** Threaded stem **Grip Length:** 1.032 mils and 1.094 centimeters Width Across Flats: Between 0.429 inches and 0.437 inches Hardness Rating: 39.0 rockwell c nut and 43.0 rockwell c nut Material: Steel comp 4140 nut or steel comp 8740 nut or steel comp 4130 nut **Material Specification:** Mil-s-5626 military specification 1st material response nut or mil-s-6049 military specification 2nd material response nut or mil-s-6758 military specification 3rd material response nut **Surface Treatment:** Cadmium sleeve and passivate sleeve **Surface Treatment Specification:** Qq-p-416, type 1, class 3 federal specification 1st treatment response sleeve and qq-p-35 federal specification 2nd treatment response sleeve **Specification Data:** 80205-nas1669 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A040a0