# NSN 5320-00-058-2312

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-058-2312

## Head Style:

Hexagon

**Head Height:** 

0.160 inches

## Shank Diameter:

Between 0.3095 inches and 0.3115 inches

# Shank Style:

Threaded self-plugging shank w/sleeve

### **Expansion Device:**

Threaded stem

### Grip Length:

1.157 mils and 1.219 centimeters

## Width Across Flats:

Between 0.429 inches and 0.437 inches

### Hardness Rating:

39.0 rockwell c nut and 43.0 rockwell c nut

## Material:

Steel comp 4140 nut or steel comp 8740 nut or steel comp 4130 nut

# Material Specification:

Mil-s-5626 military specification 1st material response nut or mil-s-6049 military specification 2nd material response nut or mil-s-6758 military

specification 3rd material response nut

# Surface Treatment:

Cadmium sleeve and passivate sleeve

## Surface Treatment Specification:

Qq-p-416, type 1, class 3 federal specification 1st treatment response sleeve and qq-p-35 federal specification 2nd treatment response sleeve

#### **Specification Data:**

80205-nas1669 professional/industrial association standard

#### Shelf Life:

N/a

# Unit Of Measure:

```
---
```

#### Demilitarization:

No

## Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.