NSN 5320-00-059-3312

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-059-3312 **Fastener Length:** 0.541 inches **Head Style:** Hexagon **Head Height:** 0.113 inches **Shank Diameter:** Between 0.197 inches and 0.199 inches **Shank Style:** Threaded self-plugging shank w/sleeve **Expansion Device:** Threaded mandrel **Grip Length:** Between 0.407 inches and 0.469 inches Width Across Flats: Between 0.305 inches and 0.312 inches **Hardness Rating:** 39.0 rockwell c nut and 43.0 rockwell c nut **Shear Strength:** 5240 double pounds per square inch Material: Steel comp 304 sleeve or steel comp 303f sleeve or steel comp 303 sleeve **Material Specification:** Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or ams 5641 assn standard 2nd material response sleeve or astm a582 assn standard 3rd material response sleeve **Surface Treatment:** Cadmium sleeve and passivate sleeve **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response nut **Specification Data:** 80205-nas1669 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** Demilitarization: No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.