
## NSN 5320-00-062-3264

Pin-rivet - Page 1 of 2





### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.037 inches and 1.057 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.095 inches and 0.097 inches

### Shank Diameter:

Between 0.254 inches and 0.255 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.390 inches and 0.395 inches

#### Grip Length:

0.572 inches

## Thready Qty Per Inch (tpi):

28

## Thread Size:

0.250 inches

## Shear Strength:

95000 single pounds per square inch

### **Countersink Angle:**

100.0 degrees

### **Special Features:**

Solid film and cetyl alcohol lubrication

### Material:

Titanium alloy

### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Anodize

### Surface Treatment Specification:

Ti-shield 3, fscm 73197 mfr ref single treatment response or tiodize type 2, fscm 73197 mfr ref single treatment response

### **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-00-062-3264

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

