## NSN 5320-00-062-3268

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-062-3268 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.402 inches and 1.422 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.127 inches and 0.130 inches **Shank Diameter:** Between 0.317 inches and 0.318 inches **Shank Style: Head Major Diameter:** Between 0.469 inches and 0.474 inches **Grip Length:** 0.822 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Solid film and cetyl alcohol lubrication Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Ti-shield 3, fscm 73197 mfr ref single treatment response or tiodize type 2, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5320-00-062-3268

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0