## NSN 5320-00-062-3274

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-062-3274 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.650 inches and 0.670 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.079 inches and 0.081 inches **Shank Diameter:** Between 0.194 inches and 0.195 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.302 inches **Grip Length:** 0.260 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Solid film and cetyl alcohol lubrication Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Ti-shield 3, fscm 73197 mfr ref single treatment response or tiodize type 2, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5320-00-062-3274

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0