

View Online at <https://aerobasegroup.com/nsn/5320-00-062-3281>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.838 inches and 0.858 inches

Head Style:

Err-090

Head Height:

Between 0.045 inches and 0.055 inches

Width Between Flats:

Between 0.079 inches and 0.081 inches

Shank Diameter:

Between 0.194 inches and 0.195 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.295 inches and 0.315 inches

End Application:

W/s: ircraft, tomcat f-14; aircraft, hawkeye e-2c; fms-aircraft, hawkeye e-2c

Grip Length:

0.448 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Shear Strength:

95000 single pounds per square inch

Special Features:

Solid film and cetyl alcohol lubrication

Material:

Titanium alloy

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Ti-shield 3, fscm 73197 mfr ref single treatment response or ti-dize type 2, fscm 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0