NSN 5320-00-062-3283

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-062-3283 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.163 inches and 1.183 inches **Head Style:** Err-090 **Head Height:** Between 0.059 inches and 0.069 inches Width Between Flats: Between 0.095 inches and 0.097 inches **Shank Diameter:** Between 0.254 inches and 0.255 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.387 inches and 0.412 inches **Grip Length:** 0.698 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch **Special Features:** Solid film and cetyl alcohol lubrication Material: Titanium alloy uns r56400 or titanium alloy **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Ti-shield 3, fscm 73197 mfr ref single treatment response or tiodize type 2, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5320-00-062-3283

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0